



CHRYSO®XeI C5

ACCELERATOR (WITH CHLORIDE)

DESCRIPTION

The plastifiant accelerators of the **CHRYSO®XeI C4** group are admixtures containing chloride, specially conceived for dry fabricated concrete. They accelerate both the setting and the hardening of concrete.

Characteristics:

- Increases the cohesion of cement and facilitates instant demoulding.
- Increases strength at all ages.
- Decrease the curing duration.

Packaging:

CHRYSO®XeI C5 is supplied in 25ltr and 200ltr non-returnable drums.
Bulk deliveries and storage tanks can also be arranged.

DIRECTIONS FOR USE

- ❑ These admixtures should be used specifically for concrete products such as blocks, paving stones, pipes, fences, pavements, curbs, etc.
- ❑ They can be used with all Portland cements.
- ❑ They should not, however be used in pre-stressed concrete or in concrete intended for floor heating.
- ❑ They should not be used for aluminous cements.

Dosage:

0,7 to 1,5ltrs / 100kg cement.

Supply:

Direct all inquiries to **CHRYSO**.

PRECAUTIONS

Safety:

CHRYSO®XeI C5 is non-toxic.

In case of contact with skin, rinse with fresh water.

In case of contact with eyes, rinse with copious quantities of fresh water and seek medical advice.

Fire:

CHRYSO®XeI C5 is non-flammable.

Spillage:

Accidental spillage may be mopped up and rinsed with fresh water.

The information contained in this document is given to the best of our knowledge and is the result of objective testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be carried out before the product is used to ensure that the methods and conditions of the use of the product are satisfactory. Our specialists remain at the disposal of the users to help with any problem they may have.