


CHRYSO® Finisol Brut

Concrete sealer for exposed aggregate concrete

Natural aspect



CHRYSO® FiniSol Brut is a water-based concrete sealer designed to protect aesthetic concrete, especially on concrete at early ages (12 to 24 hours after concrete casting). This product is particularly adapted to protect exposed aggregate concrete, on which it can be applied immediately after the wash out of the surface retarder.

CHRYSO® FiniSol Brut has a tracing effect that helps to see the treated areas and to optimize the dosage. The white aspect totally disappears when drying.

CHRYSO® FiniSol Brut is particularly appropriate to protect exposed aggregate concrete. It can be immediately applied after the washing away of the top-surface retarder.

CHRYSO® FiniSol Brut is a film-forming sealer that reduces stains and thanks to its hydrophobic and oleophobic functions, protects against water, oils and dust.

CHRYSO® FiniSol Brut improves surface toughness, abrasion and wear resistance (ISO 11-998 and ASTM D24-56) and reduces also the appearance of efflorescences.

CHRYSO® FiniSol Brut does not modify the aspect and the colour of the substrate on which it is applied. It is not yellowing in the length (Accelerated ageing test - NF EN ISO 11-507).

Its water based formulation makes it safe for users.

Indicative characteristics

- Nature: liquid
- Colour: White
- Specific gravity: 1,020
- pH: 8,00
- Freezing point: -1 °C
- COV inférieur à (Cat A – I de la Directive n° 2004-42/CE): 55 g/L
- Shelf life: 12 months

Domains of application

- Exposed aggregate concrete
- Aesthetic concrete
- Street furniture
- Precast elements
- Exposed aggregate roadworks and slabs

Precautions

Protect from frost.

Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

CHRYSO® FiniSol Brut must be applied on clean substrates, free of any water excess. In case of excess, brush them away.

Do not apply when it is wet or when temperatures are below 10 °C.

Method of use


Consumption: 150 to 250 g/m²

CHRYSO® FiniSol Brut dosage depends on the porosity of the surface to be treated. The average coverage for one coat is 1 litre for 5m².

CHRYSO® Finisol Brut

Concrete sealer for exposed aggregate concrete

Natural aspect



CHRYSO® FiniSol Brut is ready-to-use and can be applied by brush, roller or spray for both interior and exterior applications.

Apply CHRYSO® FiniSol Brut on "wet" substrate, free of any water excess (puddles...).

Apply in a uniform manner without any run-downs or puddles.

If necessary, wait 4 hours before applying a second coat, provided that ambient temperatures are not below 10° C.

Clean tools with clean water

Safety

This product is classified as "harmless". In case of exposure, it is recommended to wear your protective equipment.

Before use, refer to the safety data sheet on our internet site www.chryso.com