



# CHRYSO® Plast PR2 XL

## Plasticiser - Accelerator

### DESCRIPTION

**CHRYSO® Plast PR2 XL** is a chloride -containing, triple action admixture, which accelerates, plasticises and entrains air in dry concrete mixes. It increases strength at 24 hours by up to 30%.

**CHRYSO® Plast PR2 XL** enhances the flow properties of dry cement mixes dramatically, resulting in a significant reduction in vibration and cycle times.

**CHRYSO® Plast PR2 XL** furthermore permits the optimisation of the cement content by improving the dispersion of the cement particles with resultant improvement in the final strength and durability.

### Characteristics:

Appearance	:	Light brown liquid
Density	:	1.27
Colour	:	Light brown
pH	:	4
Freezing point	:	-15°C
Chlorine content	:	less than 200g/l (15.3%)

### Packaging:

**CHRYSO® Plast PR2 XL** is supplied in 25ltr and 200ltr non-returnable containers.

### DIRECTIONS FOR USE

#### Areas of use:

- Cement brick & blocks
- Cement pavers

#### Use and dosage:

Standard dosage:  
0.70 – 1.4 ltrs per 100kg cement.

**CHRYSO® Plast PR2 XL** can be dosed directly into the gauging water.

When the mixer is fitted with a hydrometer, the timing / dosage must be adjusted.

The use of **CHRYSO® Plast PR2 XL** is subject to the dictates of the DTU 21 – 4 regulations pertaining to the use of chloride-containing admixtures.

### Important:

If the product freezes, it will regain all its properties once thawed and mixed thoroughly.

Do not use coloured cement without consulting **CHRYSO**.

### Health and safety:

**CHRYSO® Plast PR2 XL** is classed as an irritant. The use of protective equipment for the skin and eyes is therefore recommended.

In case of spillage mop up with fresh water.

The information contained in this document is given to the best of our knowledge and is the result of objective testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be carried out before the product is used to ensure that the methods and conditions of the use of the product are satisfactory. Our specialists remain at the disposal of the users to help with any problem they may have.