


CHRYSO® Care Protec

Non adhesive protection agent



CHRYSO® Care Protec leaves a greasy film on the surface of any metallic part, which prevents the hydraulic binders from naturally sticking, thus allowing easier cleaning and effective protection from rust.

The non oxidising agents contained in **CHRYSO® Care Protec** don't modify painted steel sheets colours.

The concrete doesn't stick to the mixer's arms, which eases cleaning.

Indicative characteristics

- Nature: liquid
- Colour: Beige
- Flash point: 71 °C
- Cinematic viscosity at 20°C: 6,5 mm²/s (cSt) ± 1,5 mm²/s (cSt)
- Shelf life: 18 months

Norms and regulations

- Conforms for PCB content with legislation in force (Directives of the European Communities Council No. 85/467/CEE of 1st October 85 – OJ of the European Communities L269 of 11 October 1985).

Domains of application

- Truck protection
- Protection of pipe manufacturing equipment
- Mixer protection
- Any metallic surface in contact with cement, concrete or mortar
- Mould box protection for block machines

Precautions

Using **CHRYSO® Care Protec** in the mixer may reduce the effect of the **CHRYSO® Stab** range of products.

It is therefore highly recommended to realise a test first, if **CHRYSO® Care Protec** is in direct contact with the mixed mortar.

Method of use

Consumption: 50 m²/L on metallic surfaces.

Equipment:

Recommended nozzle type: TP 11015

Pressure: 3 bars

Nozzle colour: yellow

Metallic surfaces protection:

Spray a film of **CHRYSO® Care Protec** onto the surfaces which are to be protected.

Cleaning metallic surfaces:

Brush first, and then clean with a water hose.

After cleaning, apply another film of **CHRYSO® Care Protec**.

Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on www.chryso.com



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on www.chryso.com.

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

