# CHRYSO®QUAD 743

Water reducing plasticiser

7/10/2024

### DESCRIPTION

- CHRYSO® Quad 743 is a latest generation water reducing plasticiser, specific to an excess of fines and/or swelling clay.
- CHRYSO® Quad 743 includes some of our most recent polymer technologies. CHRYSO® Quad 743 uses CLEAR® (Clay Enabling Admixture Response) technology, allowing for efficient dispersion of hydraulic binders in concrete mix design using challenging sands containing swelling clays or high amounts of fine particles.



# **BENEFITS**

- CHRYSO<sup>®</sup> Quad 743 is compatible with all types of cement, . excluding white cement.
- Ensures effective binder dispersion by enhancing the admixture dosage rate (PCP) and increasing workability retention.
- Reduces viscosity, improving placing and good concrete finishina.
- A wide dosage range.
- Compensates for low fines aggregates.
- Strong water reduction with all aggregate packages.
- Excellent water reduction
- If no clay is present in the aggregates, additional water reduction is achieved.

# PHYSICAL and CHEMICAL PROPERTIES

| Product Nature   | Liquid                |
|------------------|-----------------------|
| Color            | Brown                 |
| Lifetime         | 12 months             |
| Water solubility | miscible              |
| рН               | 5,50 ± 2,00           |
| Specific Gravity | 1.08 ± 1              |
| Viscosity        | 20 secs (Ford #4 Cup) |

### PACKAGING

- 25 ℓ jerry can
- 200 ℓ drum
- 1000 ℓ flow bin
- Bulk delivery on request

## METHOD OF USE

- Especially recommended for ready-mix concrete
- Plastic or fluid concrete
- Aggregates where clay is present

#### Dosage :

- The optimum dosage of CHRYSO® Quad 743 can only be established by using trial tests, taking into account local conditions affecting the workability of the fresh mix and the mechanical properties required of the concrete.
- CHRYSO<sup>®</sup> Quad 743 is compatible with most CHRYSO admixtures, confirmed by a CHRYSO Quad Lab diagnosis.
- Typical dosage range is between 0.5 to 1.5 litres for 100 kg of cement

#### **Dispensing/Mixing**

- CHRYSO<sup>®</sup> Quad 743 is completely miscible in water. CHRYSO<sup>®</sup> Quad 743 must preferably be added to the water before mixing. However, CHRYSO® Quad 743 can be added at the end of the mixing cycle.
- Should the product be added to fresh concrete, into a mixing truck, it is necessary to mix at high speed and then at low speed (with a minimum of 3 minutes at each speed).

## PRECAUTIONS

#### Storage

- CHRYSO<sup>®</sup> Quad 743 has a shelf life of 12 months starting from the manufacturing date - provided no other chemicals are added to it.
- The product should be stored away from rain and frost in clean, dry tanks.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. za.chryso.com

SAINT-GOBAIN

CHRYSO Southern Africa (Pty) Ltd - Gauteng (head office): 26 Malcolm Moodie, Crescent, Jet Park, South Africa Tél.:+ 27 (0) 113959700 P.1/2

# CHRYSO®QUAD 743

Water reducing plasticiser

Chryso Concrete

Solutions

- After freezing, the properties of CHRYSO® Quad 743 can be recovered by controlled thawing and agitation.



- This product is classified as harmless. CHRYSO will provide onsite assistance when requested.

Prior to any use, please read carefully the Material Safety Data Sheets.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing, however, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. **za.chryso.com** CHRYSO Southern Africa (Pty) Ltd - Gauteng (head office): 26 Malcolm Moodie, Crescent, Jet Park, South Africa Tél.:+ 27 (0) 113959700

